



Create a Workflow ▾



Back to home

Get/Set Task Data

- **FireStart.getTaskData(identifier)**
 - Gets the value of a BusinessEntityLink
 - @param {string} identifier - Id of the BusinessEntityLink. The format of the variable has to be **Identifier**.
 - @returns {string} value
- **FireStart.setTaskData(identifier, value)**
 - Sets the value of a BusinessEntityLink
 - @param {string} identifier - Id of the BusinessEntityLink. The format of the variable has to be **Identifier** and the variable itself needs to be defined as **Output**.
 - @param {string} value - The value to be set, has to be in the internal format depending on the type of BusinessEntityLink, e.g. Date/Time

Note: The functions get/setTaskData() operate silently on the business entity field and do NOT refresh controls, that may have the same business entity field as a data context.

Example Form

This example shows how to create an HTML control that gets and displays who started the workflow and writes back some text to a workflow variable using the functions listed above.

The screenshot shows the FireStart HTML Editor interface. On the left, there's a sidebar titled "Variables" with sections for "Workflow Variables" (containing "Text" and "EXECUTION_STARTED_BY") and "System Fields" (with a checked "Show system fields" checkbox). Below this is a toolbar with "Add" and "OK" buttons. The main area is split into two panes. The left pane, titled "HTML Editor", contains the following code:

```

<!DOCTYPE html>
<html>
  <head>
    <link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/3.4.1/css/bootstrap.min.css"></link>
    <style>
      body {
        background-color: whitesmoke;
      }
    </style>
    <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.3.1/jquery.min.js"></script>
    <script>
      $(document).ready(function(){
        var startedBy = Firestart.getTaskData('Workflow Variables.EXECUTION_STARTED_BY');
        $('#startedBy_field').val(startedBy);
        $('#text_field').on('change', function() {
          Firestart.setTaskData('Workflow Variables.Text', $('#text_field').val());
        });
      });
    </script>
  </head>
  <body>
    <div class="container">
      <form>
        <div class="form-group">
          <label for="startedBy">Execution started by:</label>
          <input class="form-control" disabled id="startedBy_field"></input>
        </div>
        <div class="form-group">
          <label for="text">Text to write to Business Entity:</label>
          <input class="form-control" id="text_field"></input>
        </div>
      </form>
    </div>
  </body>
</html>

```

The right pane, titled "Preview", shows a form with two fields: "Execution started by:" (containing the value from the task data) and "Text to write to Business Entity:" (an empty input field). At the bottom are "OK" and "Cancel" buttons.

HTML

```

<!DOCTYPE html>
<html>
<head>
<link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/3.4.1/css/bootstrap.min.css"/>
<style>
body{
    background-color: whitesmoke;
}
</style>
<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.3.1/jquery.min.js">
</script>
<script>
$(document).ready(function(){
    var startedBy = FireStart.getTaskData('{##|BELINK:00000000-0000-0000-0000-000000000000{##|PARAM:##|PNAME:Ider');
    $('#startedBy_field').val(startedBy);
    $('#text_field').on('change', function() {
        FireStart.setTaskData('{##|BELINK:00000000-0000-0000-000000000000{##|PARAM:{##|PNAME:Ider');
    });
})
</script>
</head>
<body>
<div class="container">
<form>
<div class="form-group">
<label for="usr">Execution started by:</label>
<input id="startedBy_field" class="form-control" disabled/>
</div>
<div class="form-group">
<label for="usr">Text to write to Business Entity:</label>
<input class="form-control" id="text_field"/>
</div>
</form>
</div>
</body>
</html>

```

Do not forget to set the format of the used business entity links to **Identifier**.

```

$('#text_field').on('change', function() {
    FireStart.setTaskData('{##|Workflow Variables.Text @ X|PARAM:##|PNAME:Ider', $('#text_field').val());
});
</script>
</head>
<body>
<div class="container">
<form>
<div class="form-group">
<label for="usr">Execution started by:</label>
<inout class="form-control" disabled_id="startedBy_field"></inout>

```

- Internal format
- Identifier

Output format:

ID

Example:

2a821d90-a240-48bf-8d1f-d6458491c87d

Displayed below is the form during the workflow execution.



FireStart

Example

HTML get/setTaskData

Execution started by:
TSynthesis

Text to write to Business Entity:
Test value

Finish

After completing the task, the variable is now assigned the entered value.

Business entity values
Shows the current values of the selected business entity.

Workflow Variables (1)

Text: Test value

Close

